

DECLARATION OF PERFORMANCE

Nro. 003.CPR.HVK

1. Unique identification code of the product-type:

Kerabit Ridge Vent Strip

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Dimensions	Color	Product number
0,32 x 10 m	Red	16530
	Green	16531
	Grey	16532
	Brown	16533
	Black	16534
	Green/Black	16535
	Copper	16536
	White/Grey	16537
	Red/Black	16538
	Brown/Black	16539
	Redmix	16540
	Weather Wood	16541
	Brownmix	16542
	Parkland Brown	16543
	Graphite	16544
Amber Brown	16545	
Country Cedar	16546	

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

A top sheet of the ridge vent

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Kerabit Oy
Puistokatu 25 - 27, 08150 Lohja, Finland
P. 010 851 1000
www.kerabit.fi

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified factory production control certification body Eurofins Expert Services Oy No. 0809 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (No.0809-CPR-1030).

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B _{ROOF} (t2)	EN 13707: 2004+A2:2009
Reaction to fire	NPD	
Watertightness	pass	
Tensile strength		
- in longitudinal direction	750 N/50 mm, ± 150	
- in transverse direction	550 N/50 mm, ± 150	
Elongation	40 %, ± 15	
Resistance to static loading	NPD	
Resistance to impact	NPD	
Nail shank tear resistance		
- in longitudinal direction	250 N, ± 100	
- in transverse direction	300 N, ± 150	
Pliability after aging		
- surface	-15°C	
- backside	-10 °C	
Flow resistance at elevated temperature after aging	80°C	
Pliability		
- surface	- 20 °C	
- backside	- 20 °C	
Dangerous substances ¹⁾	No dangerous substances	
NPD (No Performance Determined)		

1) no asbestos or coal tar constituents

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Lohja 8.6.2023



Veijo Kangasmaa
Development and Quality Manager
Nordic Waterproofing Oy