

Kerabit

Kerabit 3300 UTL

Päivitetty 17.5.2024 Tulostettu 23.2.2025

Kerabit 3300 UTL is a line-torch-on underlay membrane in multi-layer membrane system.

The carrier consists of polyester. The underside of the product is coated with torch-applied bitumen, the top surface with sand.



Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE
Reaction to fire	Manufacturer's declaration of the fire test
Fire Classification	B _{ROOF} (t2)
Manufacturer's declaration of conformity	Kerabit modified bitumen roofing
Quality control	Quality control carried out at the Plant quality control and a quality control agreement between the Plant and Eurofins Expert Services Oy
SFS-labeling	K-TMS 170/3300 torch
Product category	TL 2
Nominal thickness	approx. 2,5 mm
Nominal weight	3300 g/m ²
Weight of the supportive layer	170 g/m ² (+/- 10 g/m ²)
Supportive layer	polyester
Surface type	sand granules
Rolls size	1 x 10 m / 10 m ²
Packages / pallet	24 rll
Weight / package	33 kg
Weight / pallet	817 kg

Additional information

Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.

Kerabit

Applications

This product can be used as an underlayer in multi-layer bitumen roofing or under discontinuous roofing as well as vapour barrier membrane.