
Kerabit

Kerabit Root Prevention Membrane



Päivitetty 7.9.2026 Tulostettu 12.11.2026

Kerabit Root Prevention Membrane Grey is a torch-on modified bitumen membrane with product classification 2 used to protect green roof waterproofing against roots. It is used as an accessory for the sand-finish Kerabit Root Prevention Membrane in, for example, upturns and other visible details that remain exposed to sun rays.

The product has a strong polyester carrier and granulated surface. The root prevention membrane is tested according to standard EN 13948 (FLL method).

Technical data

Manufacturer / Manufactured for	Axter
Country of origin	France
Conformity marking	CE
Product category	TL 2
Nominal weight	6360 g/m²
Supportive layer	polyester
Surface type	slate granules
Rolls size	1 x 7,5 m / 7,5 m²
Colours	grey
Packages / pallet	16 pcs
Weight / package	47,7 kg
Weight / pallet	788 kg

Additional information

Field of application

The product is used on green roofs and decks as an accessory for Kerabit Root Prevention Membrane in, for example, upturns and other visible details that remain exposed to sun rays.

Checklist

→ liquefied gas torch and hot work licence

This publication has been reviewed with the utmost care. However, we are not liable for any direct or indirect damages resulting from errors or the incorrect application of the information contained herein. We reserve the right to make changes. The latest version of this document is available at kerabit.fi/tuotteet.