Kerabit

Kerabit 3000 UB

Päivitetty 25.4.2023 Tulostettu 11.10.2026

Kerabit 3000 UB is a modified bitumen underlay membrane with a polyester felt as a carrier. The top and bottom surfaces are coated with sand. The 100 mm wide adhesive sections are located on the top and bottom surfaces, on opposing sides.

Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE
Reaction to fire	Manifacturer´s declaration of the fire test
Fire Classification	$B_{ROOF}(t2)$
Manufacturer's declaration of conformity	Kerabit modified bitumen roofing
Quality control	Quality control carried out at the Plant quality control and a quality control agreement between the Plant and Eurofins Expert Services Oy
Nominal thickness	2,5 mm
Nominal weight	3000 g/m²
Weight of the supportive layer	170 g/m² (+/- 10 g/m²)
Supportive layer	reinforced polyester felt
Surface type	sand granules.
Rolls size	10 x 10 m / 10 m²
Packages / pallet	31 rolls
Weight / package	30 kg
Weight / pallet	955 kg

Additional information

Applications

This product is used as an underlay for tile and metal roofs and also as a vapour-barrier.

Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.

Checklist

→ Kerabit Sealing Adhesive for seaming gable seams

This publication has been reviewed with the utmost care. However, we are not liable for any direct or indirect damages resulting from errors or the incorrect application of the information contained herein. We reserve the right to make changes. The latest version of this document is available at kerabit.fi/tuotteet.