

# Kerabit

## Kerabit 3000 UB

Päivitetty 25.4.2023 Tulostettu 3.7.2024

Kerabit 3000 UB is a modified bitumen underlay membrane with a polyester felt as a carrier. The top and bottom surfaces are coated with sand. The 100 mm wide adhesive sections are located on the top and bottom surfaces, on opposing sides.



## Technical data

<b>Manufacturer / Manufactured for</b>	Kerabit Oy, Lohja plant
<b>Country of origin</b>	Finland
<b>Conformity marking</b>	CE
<b>Reaction to fire</b>	Manufacturer's declaration of the fire test
<b>Fire Classification</b>	B <sub>ROOF</sub> (t2)
<b>Manufacturer's declaration of conformity</b>	Kerabit modified bitumen roofing
<b>Quality control</b>	Quality control carried out at the Plant quality control and a quality control agreement between the Plant and Eurofins Expert Services Oy
<b>Nominal thickness</b>	2,5 mm
<b>Nominal weight</b>	3000 g/m <sup>2</sup>
<b>Weight of the supportive layer</b>	170 g/m <sup>2</sup> (+/- 10 g/m <sup>2</sup> )
<b>Supportive layer</b>	reinforced polyester felt
<b>Surface type</b>	sand granules.
<b>Rolls size</b>	10 x 10 m / 10 m <sup>2</sup>
<b>Packages / pallet</b>	31 rolls
<b>Weight / package</b>	30 kg
<b>Weight / pallet</b>	955 kg

## Additional information

### Applications

This product is used as an underlay for tile and metal roofs and also as a vapour-barrier.

### Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.

## Checklist

→ Kerabit Sealing Adhesive for seaming gable seams