Kerabit

Kerabit Nature asphalt repair compound

Päivitetty 6.5.2024 Tulostettu 25.11.2025

The Kerabit Nature asphalt repair compound is an immediately usable and solvent-free cold repair compound for patching potholes and cracks in asphalt.

It is made from a binding agent consisting of bitumen and bio oil as well as rock aggregate. The aggregate granule size is 0–8 mm. The compound hardens as a result of the combined effect of pressure and moisture. If necessary, the material can watered before compacting to accelerate the hardening process. The ratio is 2 I of water per 20 kg of compound. The repair compound can be also be used to smooth kerbstones, repair manhole cover frames and fill in sawed grooves. The compound can be loaded immediately after installation.





Technical data

Kerabit Oy, Lohja plant	
Sweden	
20 kg / m² (as a 1 cm layer)	
20 kg	
33 buckets	
20 kg	
685 kg	
	Sweden 20 kg / m² (as a 1 cm layer) 20 kg 33 buckets 20 kg

Additional information

Instructions for use

Clear any debris from the area to be repaired carefully. Fill the spot will gravel or sand and compact the material firmly. For the repair compound, the thickness of the area to be repaired must be 1–4 cm. Spread the repair compound and, if necessary, moisten it with two litres of water per each 20 kg of compound. Compact the compound with a compactor or by driving a vehicle over it multiple times.

The product must be stored in the original packaging protected from moisture and sun.