Kerabit Katusaumo

Päivitetty 4.9.2025 Tulostettu 12.11.2026



Katusaumo is an elastic, hot-applied sealing compound containing rubber but no solvents or other substances hazardous to health.

Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja Plant
Country of origin	Finland
Need for materials	depending on target
Packages / pallet	49 pcs
Weight / package	22,5 kg
Weight / pallet	1127,5 kg

Additional information

Applications

For sealing joints and cracks in asphalt and concrete, as well as for the joints between rails and their concrete foundation.

Instructions for use

Katusaumo sealing compound must be heated using a bitumen pot equipped with a thermometer, a thermostat and an automatic heat regulation system. The temperature must not exceed 210°C. Sealing and filling the cracks is best carried out using a bitumen pouring can made for spreading bitumen. It is important that the surfaces to be repaired are dry and dust-free. When sealing, adhesion is enhanced if the surfaces are heated or if the Kerabit modified bitumen solution is applied to them.

For more detailed instructions, consult the product description.

This publication has been reviewed with the utmost care. However, we are not liable for any direct or indirect damages resulting from errors or the incorrect application of the information contained herein. We reserve the right to make changes. The latest version of this document is available at kerabit.fi/tuotteet.