


Kerabit Eaves/Ridge Shingle Easy

Päivitetty 12.7.2024 Tulostettu 2.4.2025

Kerabit Easy Eave/Ridge Shingle is a eave and ridge shingle designed to be used with Kerabit K Easy bitumen roofing. A 1-metre shingle on the ridge is cut into three pieces, rotated 90 degrees and overlapped for the length of the adhesive surface.

The carrier of the product consists of non-woven glass fibre with a modified bitumen coating on both sides. The bottom surface is coated with adhesive bitumen, the top with slate granulates or slag (black).



Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE
Quality control	Quality control carried out at the Plant quality control and a quality control agreement between the Plant and Eurofins Expert Services Oy
Nominal thickness	approx. 3,2 mm
Dimensions	1 x 0,33 m = 3 x 0,33 x 0,33 m
Nominal weight	4000 - 4400 g/m ²
Weight of the supportive layer	100 - 120 g/m ²
Supportive layer	glass fibre non-woven
Surface type	slate granulates or slag (black)
Colours	black, gray, red, brown and green
Packages / pallet	21
Weight / package	21,5 kg, black 24,2 kg
Weight / pallet	477 kg, black 534 kg

Additional information

Gain / package:

- eaves 15 linear metres
- ridge 7.4 linear metres