Kerabit

Kerabit 3200 UTL Fleece

Päivitetty 21.10.2026 Tulostettu 12.11.2026



Kerabit 3200 UTL Fleece is a line-torch-on (K-TMS 170/3200 torch-on) underlay membrane of product category 2 for multi-layer roofing. The product also serves as an underlay (AKE and AKK 1) for non-continuous roofing and as a vapour-barrier membrane (BH 1).

The carrier is of polyester. The lower surface of the product is torch-on bitumen and the upper surface is polypropylene non-woven fabric.

Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE
Reaction to fire	Manifacturer´s declaration of the fire test
Fire Classification	B_{ROOF}(t2)
Manufacturer's declaration of conformity	Kerabit modified bitumen roofing
Quality control	Quality control carried out at the Plant quality control and a quality control agreement between the Plant and Eurofins Expert Services Oy
SFS-labeling	K-TMS 170/3200 torch-on
Product category	TL 2, AKE, AKK 1, BH 1
Nominal thickness	approx. 2,6 mm
Nominal weight	3200 g/m²
Weight of the supportive layer	170 g/m² (+/- 5 g/m²)
Supportive layer	polyester
Surface type	PP non-woven fabric
Rolls size	1 x 10 m / 10 m²
Packages / pallet	24 rolls
Weight / package	32 kg
Weight / pallet	793 kg

Additional information

Applications

The product is used as an underlay membrane for multi-layer roofing, as an underlay for non-continuous roofing and as a vapour-barrier membrane.

Handling and storage

Modified bitumen membranes are stored on pallets in a dry and cool place in an upright position. The rolls must be protected with plastic hoods or tarps. In temperatures in excess of +40 °C, the rolls must be stored away from sunlight.

This publication has been reviewed with the utmost care. However, we are not liable for any direct or indirect damages resulting from errors or the incorrect application of the information contained herein. We reserve the right to make changes. The latest version of this document is available at kerabit.fi/tuotteet.