

Kerabit

Kerabit 5000 TOP FR

Päivitetty 25.4.2023 Tulostettu 2.4.2025

Kerabit 5000 TOP is a torchable (K-PS 220/5000 torch-on) top membrane of product category 2 for multi-layer roofing. The product is suitable for use with structures featuring a bitumen-laminated PIR thermal insulation with a fully attached TL 2 underlay membrane (Kerabit Base or Kerabit 3000 U). There is no need for a bearing layer of wool between PIR insulation and the underlay membrane, enabling faster installation.



Kerabit 5000 TOP FR has a reinforced polyester felt as a carrier. The bottom surface of the product features modified torch-on bitumen, and the top surface slate granules.

The product colour is grey. Kerabit 5000 TOP FR is made to order.

Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE mark
Reaction to fire	Manufacturer's fire testing certificate
Fire Classification	B _{ROOF} (t2)
Manufacturer's declaration of conformity	Kerabit modified bitumen roofing materials
Quality control	Quality control agreement between the Plant and Eurofins Expert Services Oy
Nominal thickness	approx. 4,4 mm
Nominal weight	5000 kg/m ²
Weight of the supportive layer	220 g/m ² (+/- 10 g/m ²)
Supportive layer	polyester
Surface type	slate granulates
Rolls size	1 x 8 m / 8 m ²
Colours	grey
Packages / pallet	24 rolls
Weight / package	40 kg
Weight / pallet	985 kg

Additional information

Kerabit

Handling and storage

Modified bitumen membranes are stored on pallets in a dry and cool place in an upright position. The rolls must be protected with plastic hoods or tarps. In temperatures over +40 °C, the rolls must be stored away from sunlight.

Applications

The product is used as a top membrane for multi-layer roofing.