

Kerabit 5100 T

Päivitetty 8.3.2024 Tulostettu 21.11.2024

Kerabit 5000 TOP is a torch-on top membrane in multi-layer membrane system.

The carrier consists of polyester. The underside of the product is coated with torch-on bitumen and the top side with slate.

The color options are grey, brown, green, white, red, light gray and black. Other than gray and black are made-to-order products. Also black has slate on the top side.



Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE mark
Reaction to fire	Manufacturer's fire testing certificate
Fire Classification	B _{ROOF} (t2)
Manufacturer's declaration of conformity	Kerabit modified bitumen roofing materials
Quality control	Quality control agreement between the Plant and Eurofins Expert Services Oy
Nominal thickness	approx. 4,4 mm
Nominal weight	5000 kg/m ²
Weight of the supportive layer	170 g/m ² (+/- 10 g/m ²)
Supportive layer	polyester
Surface type	slate granulates
Rolls size	1 x 8 m / 8 m ²
Colours	grey, brown, green, white, red, light gray and black (other than gray and black are made-to-order products)
Packages / pallet	24 rolls
Weight / package	40 kg
Weight / pallet	985 kg

Additional information

Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.

Kerabit

Applications

This product can be used as a top membrane of a multi-layer membrane system and as a top membrane of a multi-layer membrane system.