

Kerabit 5000 TL

Päivitetty 21.6.2023 Tulostettu 8.9.2025

Kerabit 5000 TL is a line-torch-on top membrane (K-PS 220/5000 torch-on) of product category 1, which can also be used as single-layer roofing for roof pitches 1:40.

Reinforced polyester felt serves as the carrier. The bottom surface of the product features modified torch-on bitumen, and the top surface grey slate granules.

The product has been approved for use in buildings with the Nordic Swan Ecolabel.



Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE mark
Reaction to fire	Manufacturer's fire testing certificate
Fire Classification	B _{ROOF} (t2)
Manufacturer's declaration of conformity	Kerabit modified bitumen roofing materials
Quality control	Quality control agreement between the Plant and Eurofins Expert Services Oy
Nominal thickness	approx. 4,5 mm
Nominal weight	5000 kg/m ²
Weight of the supportive layer	220 g/m ² (+/- 10 g/m ²)
Surface type	slate granulates
Rolls size	1 x 8 m / 8 m ²
Colours	grey
Packages / pallet	24 rolls
Weight / package	40 kg
Weight / pallet	985 kg

Additional information

Field of application

The product is used as single-layer roofing.

Handling and storage information

Modified bitumen membranes are stored on pallets in a dry and cool place in an upright position. The rolls must be protected with plastic hoods or tarps. In temperatures in excess of +40 °C, the rolls must be stored away from sunlight.