

Kerabit

Kerabit 5000 TL

Päivitetty 21.6.2023 Tulostettu 21.1.2025

Kerabit 5000 TL is a line-torch-on top membrane (K-PS 220/5000 torch-on) of product category 1, which can also be used as single-layer roofing for roof pitches 1:40.

Reinforced polyester felt serves as the carrier. The bottom surface of the product features modified torch-on bitumen, and the top surface grey slate granules.

The product has been approved for use in buildings with the Nordic Swan Ecolabel.



Technical data

| | |
|---|---|
| Manufacturer / Manufactured for | Kerabit Oy, Lohja plant |
| Country of origin | Finland |
| Conformity marking | CE mark |
| Reaction to fire | Manufacturer's fire testing certificate |
| Fire Classification | B _{ROOF} (t2) |
| Manufacturer's declaration of conformity | Kerabit modified bitumen roofing materials |
| Quality control | Quality control agreement between the Plant and Eurofins Expert Services Oy |
| Nominal thickness | approx. 4,5 mm |
| Nominal weight | 5000 kg/m ² |
| Weight of the supportive layer | 220 g/m ² (+/- 10 g/m ²) |
| Surface type | slate granulates |
| Rolls size | 1 x 8 m / 8 m ² |
| Colours | grey |
| Packages / pallet | 24 rolls |
| Weight / package | 40 kg |
| Weight / pallet | 985 kg |

Additional information

Field of application

The product is used as single-layer roofing.

Kerabit

Handling and storage information

Modified bitumen membranes are stored on pallets in a dry and cool place in an upright position. The rolls must be protected with plastic hoods or tarps. In temperatures in excess of +40 °C, the rolls must be stored away from sunlight.