

# Kerabit


## Kerabit 5000 TL

Päivitetty 21.6.2023 Tulostettu 22.6.2026

Kerabit 5000 TL is a line-torch-on top membrane (K-PS 220/5000 torch-on) of product category 1, which can also be used as single-layer roofing for roof pitches 1:40.

Reinforced polyester felt serves as the carrier. The bottom surface of the product features modified torch-on bitumen, and the top surface grey slate granules.

The product has been approved for use in buildings with the Nordic Swan Ecolabel.



## Technical data

<b>Manufacturer / Manufactured for</b>	Kerabit Oy, Lohja plant
<b>Country of origin</b>	Finland
<b>Conformity marking</b>	CE mark
<b>Reaction to fire</b>	Manufacturer's fire testing certificate
<b>Fire Classification</b>	B <sub>ROOF</sub> (t2)
<b>Manufacturer's declaration of conformity</b>	Kerabit modified bitumen roofing materials
<b>Quality control</b>	Quality control agreement between the Plant and Eurofins Expert Services Oy
<b>Nominal thickness</b>	approx. 4,5 mm
<b>Nominal weight</b>	5000 kg/m <sup>2</sup>
<b>Weight of the supportive layer</b>	220 g/m <sup>2</sup> (+/- 10 g/m <sup>2</sup> )
<b>Surface type</b>	slate granulates
<b>Rolls size</b>	1 x 8 m / 8 m <sup>2</sup>
<b>Colours</b>	grey
<b>Packages / pallet</b>	24 rolls
<b>Weight / package</b>	40 kg
<b>Weight / pallet</b>	985 kg

## Additional information

### Field of application

The product is used as single-layer roofing.

# Kerabit

---

## Handling and storage information

Modified bitumen membranes are stored on pallets in a dry and cool place in an upright position. The rolls must be protected with plastic hoods or tarps. In temperatures in excess of +40 °C, the rolls must be stored away from sunlight.