

# Kerabit

## Kerabit 5500 T

Päivitetty 6.11.2024 Tulostettu 2.4.2025

Kerabit 5500 T is a torch-on top membrane that can also be used as a single-layer membrane.

SBS modified bitumen membrane with polyester carrier. The underside of the product is coated with torch-on bitumen and the top side with slate (grey and red) or slate granulates /slag (black).

Colour red is made to order only.



## Technical data

<b>Manufacturer / Manufactured for</b>	Kerabit Oy, Lohja plant
<b>Country of origin</b>	Finland
<b>Conformity marking</b>	CE mark
<b>Reaction to fire</b>	Manufacturer's fire testing certificate
<b>Fire Classification</b>	B <sub>ROOF</sub> (t2)
<b>Manufacturer's declaration of conformity</b>	Kerabit modified bitumen roofing materials
<b>Quality control</b>	Quality control agreement between the Plant and Eurofins Expert Services Oy
<b>Nominal thickness</b>	approx. 4,5 mm
<b>Nominal weight</b>	5500 g/m <sup>2</sup>
<b>Weight of the supportive layer</b>	220 g/m <sup>2</sup> (+/- 10 g/m <sup>2</sup> )
<b>Surface type</b>	slate granulates
<b>Rolls size</b>	1 x 8 m / 8 m <sup>2</sup>
<b>Colours</b>	Grey, black and red
<b>Packages / pallet</b>	24 rolls
<b>Weight / package</b>	44 - 48 kg
<b>Weight / pallet</b>	1081 - 1177 kg

## Additional information

### Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.

# Kerabit

---

## Applications

This product can be used as a top membrane of a multi-layer membrane system and as a single-layer membrane.