

Kerabit

Kerabit 5500 T

Päivitetty 6.11.2024 Tulostettu 23.2.2025

Kerabit 5500 T is a torch-on top membrane that can also be used as a single-layer membrane.

SBS modified bitumen membrane with polyester carrier. The underside of the product is coated with torch-on bitumen and the top side with slate (grey and red) or slate granulates /slag (black).

Colour red is made to order only.



Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE mark
Reaction to fire	Manufacturer's fire testing certificate
Fire Classification	B _{ROOF} (t2)
Manufacturer's declaration of conformity	Kerabit modified bitumen roofing materials
Quality control	Quality control agreement between the Plant and Eurofins Expert Services Oy
Nominal thickness	approx. 4,5 mm
Nominal weight	5500 g/m ²
Weight of the supportive layer	220 g/m ² (+/- 10 g/m ²)
Surface type	slate granulates
Rolls size	1 x 8 m / 8 m ²
Colours	Grey, black and red
Packages / pallet	24 rolls
Weight / package	44 - 48 kg
Weight / pallet	1081 - 1177 kg

Additional information

Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.

Kerabit

Applications

This product can be used as a top membrane of a multi-layer membrane system and as a single-layer membrane.