

Kerabit 5100 T

Päivitetty 22.5.2023 Tulostettu 14.4.2024

Kerabit 5100 T is a torch-on top membrane in multi-layer membrane system.

The carrier consists of polyester. The underside of the product is coated with torch-on bitumen and the top side with slate.

The colour options are grey, red, black, green and brown. Green and brown are made to order only.



Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE mark
Reaction to fire	Manufacturer's fire testing certificate
Fire Classification	B _{ROOF} (t2)
Manufacturer's declaration of conformity	Kerabit modified bitumen roofing materials
Quality control	Quality control agreement between the Plant and Eurofins Expert Services Oy
Nominal thickness	approx. 4,4 mm
Nominal weight	5000 kg/m ²
Weight of the supportive layer	170 g/m ² (+/- 10 g/m ²)
Supportive layer	polyester
Surface type	slate granulates
Rolls size	1 x 8 m / 8 m ²
Colours	grey, red, black, green and brown (green and brown are made to order only)
Packages / pallet	24 rolls
Weight / package	40 kg, black 43,2 kg
Weight / pallet	985 kg, black 1062 kg

Additional information

Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.

Applications

This product can be used as a top membrane of a multi-layer membrane system and as a top membrane of a multi-layer membrane system.