Kerabit 700 UB

Päivitetty 25.4.2023 Tulostettu 12.11.2026



Kerabit 700 UB is a bituminous underlay, that can be used laid on solid wood underlays or as a hanging, step-resistant underlay.

Both sides of the underlay are covered with a polypropylene fabric. This underlay has an adhesive edge. The surface has no sand.

Kerabit 700 UB can be used as an underlay for tin and tile roofings as well as bitumen shingles.

This product is diffusion-proof, therefore requiring ventilation in the space below the underlay.

Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Sweden
Conformity marking	CE
Nominal weight	700 g/m²
Supportive layer	polyester
Surface type	polypropylene weave
Rolls size	1,0 x 30 m / 30 m²
Surface bitumen	SBS modified bitumen
Colours	black
Packages / pallet	24 pcs
Weight / package	21 kg
Weight / pallet	529 kg

Additional information

Installation to be made on a solid underlay

Kerabit 700 UB is laid over tongue-and-groove boards or building boards suitable for the purpose, parallel to the ridge. Installation is carried out by nailing the underlay in place along the adhesive edge using concealed nailing.

Indicative suitability for different water roof materials:

→ bitumen shingles, inclination 1:5 or steeper
→ machine-seamed tin roofing, inclination 1:10 or steeper
→ tile roofing, inclination 1:5 or steeper.

Check the inclination and materials in the construction plan.

Installation in hanging solutions

The underlay is always laid perpendicular to roof trusses. In hanging solutions, the inclination must be at least 1:4 (14). The distance between the roof trusses must be no longer than 1200 mm. The underlay is laid in such a way that it hangs down 10 to 20 mm between the roof trusses.

Handling and storage information

Modified bitumen membranes are stored on pallets in a dry and cool place in an upright position. The rolls must be protected with plastic hoods or tarps. In temperatures in excess of +40 °C, the rolls must be stored away from sunlight.

Checklist

→ Kerabit Sealing Adhesive for seaming gable seams

This publication has been reviewed with the utmost care. However, we are not liable for any direct or indirect damages resulting from errors or the incorrect application of the information contained herein. We reserve the right to make changes. The latest version of this document is available at kerabit.fi/tuotteet.