

Kerabit

Kerabit Protect

Päivitetty 25.4.2023 Tulostettu 2.4.2025

Kerabit Protect is a diffusion-open underlay. This product consists of two layers of polypropylene fabric interlayered by a microporous polypropylene sheet.

Kerabit Protect can be installed directly on the surface of thermal insulation. However, a provision must be made for a ventilation gap between the roofing and the underlay.



Technical data

| | |
|--|--------------------------------|
| Manufacturer / Manufactured for | Kerabit Oy, Lohja plant |
| Country of origin | Czech |
| Conformity marking | CE |
| Fire Classification | category E |
| Nominal weight | 132 g/m ² |
| Rolls size | 1,5 x 50 m / 75 m ² |
| Colours | grey |
| Packages / pallet | 36 rlls |
| Weight / package | 9,7 kg |
| Weight / pallet | 375 kg |

Additional information

Application

Kerabit Protect underlay can be used on roof pitches of 1:3 and steeper. Tightness can be ensured by glueing the seams with a mesh-reinforced Kerabit Butyl Strip, laid between the lengths of the underlay, or by glueing Isola Wind Barrier Tape over the seams. The overlaps must be at least 15 cm.

Kerabit Protect is installed longitudinally, starting from the eaves. Before the installation of the first length of the underlay, a supportive board and an eave flashing must be installed on the lower section of the roof plane.

Handling and storage information

Underlay rolls should be kept protected from the weather and sunlight.

Checklist

- Tyvek Windbarrier tape for seaming, repairing and waterproofing the underlay
- Isola FlexWrap for fastening the underlay to a chimney and for lead-throughs.
- Kerabit Butyl Strip for fastening the underlay to the eaves flashings and the laths and the underlay