

# Kerabit

## Kerabit 2400 UB

Päivitetty 25.4.2023 Tulostettu 4.7.2026

SBS modified bitumen membrane with reinforced polyester carrier. Sand granules on both side of the membrane. The under and top side 100 mm wide adhesive edges are on opposite sides.



### Technical data

<b>Manufacturer / Manufactured for</b>	Kerabit Oy, Lohja plant
<b>Country of origin</b>	Finland
<b>Conformity marking</b>	CE mark
<b>Reaction to fire</b>	Manufacturer's fire testing certificate
<b>Fire Classification</b>	B <sub>ROOF</sub> (t2)
<b>Manufacturer's declaration of conformity</b>	Kerabit modified bitumen roofing materials
<b>Quality control</b>	Quality control agreement between the Plant and Eurofins Expert Services Oy
<b>Nominal thickness</b>	2,2 mm
<b>Nominal weight</b>	2400 g/m <sup>2</sup>
<b>Weight of the supportive layer</b>	150 g/m <sup>2</sup> (+/- 5 g/m <sup>2</sup> )
<b>Supportive layer</b>	reinforced polyester felt
<b>Surface type</b>	sand granules
<b>Rolls size</b>	1 x 10 m / 10 m <sup>2</sup>
<b>Packages / pallet</b>	31 rolls
<b>Weight / package</b>	24 kg
<b>Weight / pallet</b>	769 kg

### Additional information

#### Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.

#### Applications

The product is used as underlay or intermediate layer of multi-layer roofing and underlay for bitumen shingles.

## Checklist

→ Kerabit Sealing Adhesive for seaming gable seams