# Kerabit

# Kerabit 3000 UB

Päivitetty 25.4.2023 Tulostettu 12.11.2026



Kerabit 3000 UB is a modified bitumen underlay membrane with a polyester felt as a carrier. The top and bottom surfaces are coated with sand. The 100 mm wide adhesive sections are located on the top and bottom surfaces, on opposing sides.

## Technical data

| | |
|---|---|
| **Manufacturer / Manufactured for** | Kerabit Oy, Lohja plant |
| **Country of origin** | Finland |
| **Conformity marking** | CE |
| **Reaction to fire** | Manifacturer´s declaration of the fire test |
| **Fire Classification** | $B_{ROOF}(t2)$ |
| **Manufacturer's declaration of conformity** | Kerabit modified bitumen roofing |
| **Quality control** | Quality control carried out at the Plant quality control and a quality control agreement between the Plant and Eurofins Expert Services Oy |
| **Nominal thickness** | 2,5 mm |
| **Nominal weight** | 3000 g/m² |
| **Weight of the supportive layer** | 170 g/m² (+/- 10 g/m²) |
| **Supportive layer** | reinforced polyester felt |
| **Surface type** | sand granules. |
| **Rolls size** | 10 x 10 m / 10 m² |
| **Packages / pallet** | 31 rolls |
| **Weight / package** | 30 kg |
| **Weight / pallet** | 955 kg |

## Additional information

### Applications

This product is used as an underlay for tile and metal roofs and also as a vapour-barrier.

### Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.

## Checklist

→ Kerabit Sealing Adhesive for seaming gable seams

This publication has been reviewed with the utmost care. However, we are not liable for any direct or indirect damages resulting from errors or the incorrect application of the information contained herein. We reserve the right to make changes. The latest version of this document is available at kerabit.fi/tuotteet.